

MINI SHEARS DTX 200

The Cutting Edge



Brief Description

Bench top oil hydraulic mini-shear with single or three phase electric motor. Bronze bearings throughout.

Features

- Four sided reversible serrated blades.
- Tank mounted motor.
- · Tool kit included
- Supplied ready to work.
- Foot pedal control single or automatic stroke.
- Compact with parts accessible for easy service.
- Materials hold-down and guard both fully adjustable.

Deltax reserves the right to alter the product specification in any way without giving prior notification.

Specification	Dimension	DTX 200
Overall	Length	952mm (37½")
	Width	596mm (23½")
	Height	670mm (26½")
	Weight	265kg
Blade	Length	203mm (8")
	Opening	127mm (5")
Blade Table (from bench top)	Height	407mm (16")
Max Shear Force	Tonnes Force	40
Shear Capacity	Steel Round Bar 45 kg/mm	25 (1")
Oil	ISO 46	50ltr (11 Gall)
Horsepower	Single Phase	3HP (2.2kW)
	Three Phase	5.5HP (4kW)
Speed	Single Phase	10 - 32 cuts/min
	Three Phase	20 - 60 cuts/min

Deltax Limited

6, Bottings Ind. Est., Curdridge, Botley, Hants, SO30 2DY, England UK

Tel: +44 (0)1489 784 711 Fax: +44 (0)1489 784 340 Web: www.deltax.co.uk Email: deltax@btconnect.com